

ZIRCO-BURN[®]



Zirconium Furnace Unit



High quality
at reasonable price

ZIRCO BURN®

Zirconium Furnace Unit



- Easy programmable
- High quality heating elements
- Process monitoring

TECHNICAL DATA

Main voltage and frequency	230V, 50/60 Hz
Power consumption	3000 W
Temperature max.	1600 °C
Firing chamber	Ø 116x133 mm
Weight	72 kg
Dimensions (Width x Height x Depth)	510 x 760 x 400 mm



- Order No.: 75-0000

Zirconium Blank Pidental

	Ultra High Translucent (UHT)	High Translucent (HT)	High Strength (HS)
Benefits	49% Translucency Viable alternative to Lithium Disilicate	Highest fracture toughness on the dental market. Very versatile material	Our highest strength zirconia Low translucency to cover abutments
Usage	Monolithic anterior and posterior restorations	Full contour and frameworks	Frameworks
Colors	White Pre-shaded (Coming Soon)	White Pre-shaded (H1, H2, H3, H4)	White Pre-shaded (S1, S2, S3, S4)
Systems & Sizes	71, 95, 98, 100 12mm, 14mm, 16mm, 18mm, 20mm, 25mm	71, 95, 98, 100 12mm, 14mm, 16mm, 18mm, 20mm, 25mm	71, 95, 98, 101 12mm, 14mm, 16mm, 18mm, 20mm, 25mm



2017

Published with the support of:



HUNGARIAN
INVESTMENT AND
TRADE AGENCY



PI DENTAL FOGÁSZATI GYÁRTÓ KFT. (MANUFACTURING CO. LTD.)
H-1141 Budapest, Szugló u. 83-85., Hungary • Phone: +36 1 2514944, +36 1 3632234
Fax: +36 1 2514891 • E-mail: sales.pidental@pidental.hu • www.pidental.hu